


# THE WIDE RANGE OF UV - IR TECHNOLOGY



## UV-1260 Colour ComPort Radiometer + Dosimeter


- + choice of a combination of two different spectral ranges:
- + UV-A intensity  $mW/cm^2$  + UV-V dose  $mJ/cm^2$
- + UV-B intensity  $mW/cm^2$  + UV-V dose  $mJ/cm^2$
- + UV-C intensity  $mW/cm^2$  + UV-A dose  $mJ/cm^2$
- + UV-V intensity  $mW/cm^2$  + UV-V dose  $mJ/cm^2$
- + temperature measuring °C/°F
- + big colour graphic display
- + numerical and graphical display
- + permanent or „triggered“ measuring mode\*
- + USB ComPort and PC evaluation software



The **UV-1260 Colour ComPort Radiometer + Dosimeter** is a self-contained, high quality UV measuring instrument. It is designed to measure and record UV intensity, UV dosage and temperature in the UV curing process. Measuring results are indicated both, graphically and numerically on a big colour display.

It is equipped with two different UV sensors for the individual measuring of a combination of either

- UV-A 315 – 410 nm
- UV-B 280 – 315 nm
- UV-C 230 – 280 nm
- UV-V 395 – 445 nm
- UV - 230 – 410 nm



With these two different UV-bands many of the measuring requirements of UV curing applications can be covered.

Due to its two different UV sensors and the integrated microprocessor the **UV-1260 Colour Radiometer + Dosimeter** can measure, record and display the peak of the UV-intensity ( $mW/cm^2$ ) for each UV-band individually plus the peak of total UV energy.

Additionally, this instrument is calculating the UV-dosage ( $mJ/cm^2$ ) of the UV energy supplied during the time of exposure of one measuring cycle. The UV-dosage is calculated for each UV-band (UV-A, UV-B and UV-C or UV-V) individually and as total Integral of UV-dosage over all three UV-bands. This allows to determine not only the total energy, but also how that energy is delivered, i.e., what intensity and dose at what UV-band.

With an extra sensor for measuring temperatures from 0 to 230° F / 0 to 110° C.

\*This instrument features a selectable „triggered mode“, i.e. the 30 sec recording cycle starts within a 120 second readiness phase not before the incident UV-intensity exceeds 2  $mW/cm^2$ .

The three sensors are on the back of the unit which also serves as a heat shield. After completion of the measuring cycle the measuring results are instantly displayed numerically and graphically auto-scaled on the built in 45 x 34 mm (1.75" x 1.3") TFT colour display.

A special AUTO-OFF feature that turns off the unit automatically after one minute serves as energy saving and extension of the battery service life.

The **UV-1260 Colour ComPort Radiometer + Dosimeter** comes with an USB ComPort and an evaluation software for downloading the data to a computer to show, edit and store a history of the measuring results of the entire measuring cycle as graphic charts ( $mW/cm^2$ ) and ( $mJ/cm^2$ ) and (°C/°F)

The following versions are available:

- 63.6.1. UV-1261 Colour ComPort Radiometer + Dosimeter UV-A + UV-V
- 63.6.2. UV-1262 Colour ComPort Radiometer + Dosimeter UV-A + UV-B
- 63.6.3. UV-1263 Colour ComPort Radiometer + Dosimeter UV + UV-A
- 63.6.4. UV-1264 Colour ComPort Radiometer + Dosimeter UV + UV-B
- 63.6.5. UV-1265 Colour ComPort Radiometer + Dosimeter UV + UV-V
- 63.6.6. UV-1266 Colour ComPort Radiometer + Dosimeter UV-B + UV-V
- 63.6.7. UV-1267 Colour ComPort Radiometer + Dosimeter UV-C + UV-V

Subject to change without prior notice © 2007-08

## UV-IR TECHNOLOGY

Talstr. 37 \* D-63128 Dietzenbach \* Germany  
Tel. +49(0)6074 483079 Fax +49(0)6074 483078  
www.uv-ir-technology.de \* mail: info@uv-ir-technology.de

# THE WIDE RANGE OF UV - IR TECHNOLOGY







## UV-1260 Colour ComPort Radiometer + Dosimeter

### Technical Data:

Spectral ranges:	UV-A 315 – 410 nm UV-V 395 – 445 nm UV-B 280 – 315 nm UV-C 230 – 280 nm
Max. Power Input	0 to 5,000 mW/cm <sup>2</sup>
Measuring range:	0 to 2,000 mW/cm <sup>2</sup> or 2,000 to 5,000 mW/cm <sup>2</sup>
Sampling rate:	0.005 sec (200/sec)
Recording cycle:	30 sec.
Readiness phase:	120 sec.
Display range:	0 to 36,000 mJ/cm <sup>2</sup>
Display:	TFT Colour Display, 45 x 34 mm (1.75" x 1.3")
Power source:	2 x long life 3.6 V Lithium Battery
Power consumption:	20 µA
Battery service life:	2,000 measuring cycles
Dimensions:	Ø 5.5" (140 mm), height ½" (13 mm)
Weight:	approx. 17.5 ounce (500 g)
Operating temperature:	32° to 113° F / 0 to 45° Celsius
Heat protection:	Heat shield on back plate
Base Accuracy:	± 5 %

### Special Feature:

ComPort for the download of data to a Computer



While on the conveyer belt, the **UV-1260 Colour ComPort Radiometer + Dosimeter** can withstand max. 230° F / 110° C for up to 10 seconds. The temperature of the housing should not exceed 113° F / 45° C. Because of uneven radiation distribution of the UV light source and different type of construction of the measuring devices by different manufacturers, different readings may appear under the same measurement conditions.

### Calibration:

In order to keep its full function and precision it is recommended to have re-calibration done once per year. Re-calibration will also be necessary after change of battery. PTB traceable calibration acc. to DIN EN ISO / IEC 17025 with certificate